

Herasafe 2030i BSC Ordering Information			EN 12469				NSF/ANSI 49	
<b>Dimensions</b>								
Size/Internal width		m (ft)	0.9 (3)	1.2 (4)	1.5 (5)	1.8 (6)	1.2 (4)	1.8 (6)
External Dimension (Cabinet only)	depth	mm (in.)	800 (31.5)	800 (31.5)	800 (31.5)	800 (31.5)	800 (31.5)	800 (31.5)
	width	mm (in.)	1000 (39.4)	1300 (51.2)	1600 (63.0)	1900 (74.8)	1300 (51.2)	1900 (74.8)
	height	mm (in.)	1536 (60.5)	1536 (60.5)	1536 (60.5)	1536 (60.5)	1536 (60.5)	1536 (60.5)
Usable Work Surface (net, without air intake grill)	depth	mm (in.)	465 (18.3)	465 (18.3)	465 (18.3)	465 (18.3)	465 (18.3)	465 (18.3)
	width	mm (in.)	900 (35.4)	1200 (47.2)	1500 (59.1)	1800 (70.9)	1200 (47.2)	1800 (70.9)
Shipping Dimension	depth	mm (in.)	925 (36.4)	925 (36.4)	925 (36.4)	925 (36.4)	925 (36.4)	925 (36.4)
	width	mm (in.)	1110 (43.7)	1410 (55.5)	1710 (67.3)	2010 (79.1)	1410 (55.5)	2010 (79.1)
	height	mm (in.)	1710 (67.3)	1710 (67.3)	1710 (67.3)	1710 (67.3)	1710 (67.3)	1710 (67.3)
Working height of front window		mm (in.)	200 (8)				250 (10)	
Maximum window opening (for cleaning, loading/unloading)		mm (in.)	773 (30.4)	773 (30.4)	773 (30.4)	773 (30.4)	773 (30.4)	773 (30.4)
Work surface height		mm (in.)	750-950 (29.5-37.4)				750-950 (29.5-37.4)	
<b>Weight</b>								
Net weight		kg (lbs)	170 (375)	200 (441)	230 (507)	280 (617)	200 (441)	280 (617)
Shipping weight		kg (lbs)	190 (419)	225 (496)	260 (573)	315 (694)	225 (496)	315 (694)
Max load capacity of one-piece work surface		kg (lbs)	50 (110)	50 (110)	50 (110)	50 (110)	50 (110)	50 (110)
Max load capacity of single segmented work surfaces (per 30cm segment)		kg (lbs)	25 (55)	25 (55)	25 (55)	25 (55)	25 (55)	25 (55)
<b>Electrical Data</b>								
Voltage		V	230				120	
Hertz		Hz	50/60				60	
Protection class			1/IP20					
<b>Filter Specification</b>								
Specification			H14 HEPA EN1822, 99.995% MPPS					
<b>Certifications</b>								
Standard			EN 12469				NSF/ANSI 49	
Agency certified			TÜV *	TÜV	TÜV *	TÜV	NSF	
NF Certification by LNE (France only)				51901254				
<b>Ergonomics and Utilities</b>								
Lighting intensity		lux (fc)	1000 (93)	929 (86)	1500 (139)	1418 (132)	850 (79)	1300 (121)
Interior outlets		pcs.	2 rear wall		4 rear wall		2 rear wall	4 rear wall
Service valve ports		pcs.	2 on each side + Smart Port				2 on each side + Smart Port	
Slope of front window		degree °	10				10	
<b>Herasafe 2030i Specifications</b>								
Noise level (measured according to EN 12469) 200mm opening		dB (A)	57		57			
Noise level (EN units measured according to EN 12469, NSF units measured according to NSF/ANSI 49) 250mm opening			57		58		62	62
Power consumption (in normal operation, fans on, lights on) 200mm opening		W/h	133	153	217	251		
Power consumption (in normal operation, Fans on, lights on) 250mm opening			155	175	240	300	180	316
Power consumption (in stand-by mode)		W/h	55	55	80	80	55	80
Normal heat output in operation mode (non-vented) 200mm opening		W/h	133	153	217	251		
Normal heat output in operation mode (non-vented) 250mm opening			155	175	240	300	180	316
Stand-by heat output (lights off, non-vented)		W/h	55	55	80	80	55	80
Size/Internal width		m (ft)	0.9 (3)	1.2 (4)	1.5 (5)	1.8 (6)	1.2 (4)	1.8 (6)
<b>Exhaust Volumes</b>								
Exhaust volume of cabinet 200mm opening		m <sup>3</sup> /h (cf/m)	288 (169)	386 (227)	483 (284)	580 (341)		
Exhaust volume of cabinet 250mm opening		m <sup>3</sup> /h (cf/m)	370 (215)	365 (291)	486 (286)	729 (429)	582 (342)	872 (513)
Exhaust volume, thimble ducting 200mm opening		m <sup>3</sup> /h (cf/m)	385 (226)	513 (302)	608 (358)	770 (453)		
Exhaust volume, thimble ducting 250mm opening		m <sup>3</sup> /h (cf/m)	481 (283)	642 (378)	802 (472)	963 (567)	756 (445)	1134 (667)

\* TÜV available for models with 200mm access opening

Herasafe 2030i Ordering Information		EN 12469				NSF/ANSI 49	
Size/Internal width	m (ft)	0.9 (3)	1.2 (4)	1.5 (5)	1.8 (6)	1.2 (4)	1.8 (6)
200mm Sash with Cross Beam UV-C in side walls		51032328	51032329	51032330	51032331		
200mm Sash – no options included** (250mm/10" sash can be optioned)		51032324	51032325	51032326	51032327		
250mm (10") Sash with Cross Beam UV-C in side walls, indented single piece work tray and prep for 3x rear wall mount service taps						51032334	51032335
250mm (10") Sash, indented single piece work tray						51032332	51032333
Window operating aperture 10" (250mm)	Option	51901247**				Standard	

#### Receptacle Options

Country configurations are available to ensure correct line cord and internal receptacles are shipped with the cabinet. Standard version for EN12469 cabinets is Schuko, and for NSF cabinets is type B

Country version Switzerland	Option	51900300					
Country version UK	Option	51900303					
Country version Italy	Option	51900306					
Country version FR/B/CZ/SK/PL	Option	51900921					
Country version Australia	Option	51900449					
Country version Denmark	Option	51900481					
Country version China	Option	51900900				51900900 (230V)	
Country version Israel	Option	51901255					
Country version India	Option	51901261				51901261 (230V)	
Country version Argentina	Option					51900308 (230V)	
Country version Chile	Option					51901259 (230V)	
Country version Brazil	Option					51901260 (230V)	
Country version Korea	Option					51901324 (230V)	
Country version Hong Kong & SEA	Option					51901327 (230V)	

#### Stand Options

We recommend ordering a base stand to ensure a robust and stable installation of the BSC. All of our base stands have been tested with our units for stability and functionality. Choose between a fixed height, manually adjustable working height, or electrically adjustable working height. Please consider the total height of the room when choosing the right working height. Footrest and castor options are available for added convenience.

Fixed height stand charcoal grey Provides work height of 750mm	Acc.	50155665	50155666	50155667	50155668	50155666	50155668
Adjustable height stand charcoal grey Provides work height of 750-950mm	Acc.	50155688	50155689	50155690	50155691	50155689	50155691
Electric Adjustable Stand grey-white (RAL 9002)	Acc.	50117449	50109314	50117450	50109325	50109314	50109325
Footrest bar (for non-electric floorstand)	Acc.	50051982	50051983	50051984	50051985	50051983	50051985
Castor-Set for Stand grey-white (4 pcs.) (RAL9002) Provides work height of 850 mm (for fixed stands only)	Acc.	50109977				50109977	

#### Work Surface Options

You have the option to fully customize your new BSC to accommodate any work task. The standard EN cabinet includes our stainless steel segmented worktray for easy removal, autoclaving, and cleaning under the work surface. The standard NSF cabinet includes our stainless steel single piece indented worktray. To customize your work area, order the part number to remove the standard worktray and configure the cabinet as desired. All internal surfaces and worktrays are 316 SS.

Without table tops (negative price)		Option	51900651	51900652	51900653	51900654	51900652	51900654
Flat worksurface module (150 mm)	KAM15	Acc.	50073666				50073666	
Flat worksurface module (300 mm)	KAM30	Acc.	50072685				50072685	
Flat worksurface module (600 mm)	KAM60	Acc.	50073667				50073667	
Flat worksurface module (900 mm)	KAM90	Acc.	50076398				50076398	
Flat worksurface module (1200mm)	KAM120	Acc.	No	50082970			50082970	
Flat worksurface module (1500mm)	KAM150	Acc.	No		50122210		50122210	
Flat worksurface module (1800mm)	KAM180	Acc.	No			50085281	50085281	
Lowered worksurface module (600 mm)	KAML60	Acc.	50073668				50073668	
Lowered worksurface module (900 mm)	KAML90	Acc.	50073669				50073669	
Lowered worksurface module (1200 mm)	KAML120	Acc.	No	50073670			50073670	
Lowered worksurface module (1500 mm)	KAML150	Acc.	No		50073671		No	50073671
Lowered worksurface module (1800 mm)	KAML180	Acc.	No			50078750	No	50078750
Vibration dampened surface module with granite plate (300 mm)	KAMW30	Acc.	50073757				50073757	
Vibration dampened surface module with granite plate (600 mm)	KAMW60	Acc.	50076162				50076162	

Herasafe 2030i Ordering Information		EN 12469				NSF/ANSI 49		
Size/Internal width		m (ft)	0.9 (3)	1.2 (4)	1.5 (5)	1.8 (6)	1.2 (4)	1.8 (6)
3 liter mini-sink table top module	KAMS30	Acc.		NSF only			50078875	
Replacement armrests KAS 30 (Set of 2 armrests 316 SS)	KAS 30			50073663			50073663	
Padded armrest 316 SS (Set of 2 including gel inserts)		Acc.		50156438			50156438	
Replacement gel pads for padded armrest (2 pcs.)		Acc.		50156437			50156437	

#### Additional Filter Options

Additional exhaust HEPA filters (AEF) can be fitted to the top of the BSC to provide 99.99999975% cumulative exhaust filtration. Please note that AEF filters are not a requirement for recirculating BSC's, even in the UK, where BS5726 has been superseded by EN12469, since 2000. Additional exhaust carbon filters can be fitted on top of the BSC, but should only be used for traces of solvents being used as an adjunct to microbiological study.

Additional exhaust HEPA Filter, retro-fit	KAEF	Acc.	50078857	50073772	50078856			
Additional exhaust Carbon Filter, retro-fit	KAEFC	Acc.	50078783	50073773	50078784			
Grid filter set, G1 acc. To EN 779 (5 pcs)			50076846		50076921		50076846	50076921

#### UV Options

The UV control function is designed to preserve bulb life whilst monitoring constantly. The light is programmable via the user interface. This feature measures and tracks UV bulb use ensuring that the bulbs will not require excessive replacement due to premature and unnecessary degradation. Additionally by monitoring UV bulb age, the system auto-adjusts run time to ensure consistent sterilisation.

Cross beam UV-C light option in side walls includes protective cover							
Included in models: 51032328, 51032329, 51032330, 51032331	Standard	Standard (Cross Beam - in side walls)					
Available for models: 51032324, 51032325, 51032326, 51032327	Option	51900642 (Cross Beam - in side walls)					
Included in models: 51032334, 51032335	Standard	Standard (cross beam - in side walls)					
Available for models: 51032332, 51032333	Option	51900642 (cross beam - in side walls)					

#### Media Valves

Our standard BSCs feature a dual-side wall negative pressure design which allows the user to install service valves through the side access ports. We also offer factory-installed piping options on our premium units to connect utilities to the top of the BSC to conserve right to left exterior footprint.

#### Rear Wall Media Connections

3 utility connectors prep (rear wall)  
Select rear wall service taps additionally from table below:

Available for models: 51032324, 51032325, 51032326, 51032327, 51032328, 51032329, 51032330, 51032331	Option	51901251 (G3/8")					
Included in models: 51032334, 51032335	Standard	Included					
Available for models: 51032332, 51032333	Option	51901252 (NPT3/8")					

#### Rear Wall Service Taps/Media Valves (supplies are connected above BSC)

Combustible gas tap for rear wall	Acc.	50068235				50068235
Non-combustible gas tap for rear wall	Acc.	50068234				50068234
Water tap for rear wall	Acc.	50068233				50068233
Vacuum tap for rear wall	Acc.	50068232				50068232

#### Side Wall Service Taps/Media Valves/Lead Throughs

Combustible gas tap for side wall	Acc.	50046015				50046015
Non-combustible gas tap for side wall	Acc.	50045959				50045959
Water tap for side wall	Acc.	50044679				50044679
Vacuum tap for side wall	Acc.	50044678				50044678
Hose connection for side wall, hose dia. 10-13mm	Acc.	50059017				50059017
Hose connection for side wall, hose dia. 3mm	Acc.	50076408				50076408
Hose connection for side wall, hose dia. 6/3mm	Acc.	50066668				50066668

#### Solenoid Valve (should be quoted with combustible gas G3/8 connection)

Solenoid valve for combustible gas tap	Acc.	50109978				50164922
--	------	----------	--	--	--	----------

#### Exhaust Duct Connection Kits

HEPA filters do a great job of trapping particles and biohazards, but they do not trap gases and toxic chemicals that may be used as an adjunct to microbiological studies. In these applications, it is important to select an exhaust duct transition to route exhaust air out of the laboratory to the external environment. We offer two different connections that can be installed in three different ways, depending upon facility requirements.

Thimble Duct Exhaust Transition (Connection diameter 200mm/8")	KTD	Acc.	50078796	50073770	50078795	50073770	50078795
--	-----	------	----------	----------	----------	----------	----------

Herasafe 2030i BSC Ordering Information		EN 12469					NSF/ANSI 49	
Size/Internal width		m (ft)	0.9 (3)	1.2 (4)	1.5 (5)	1.8 (6)	1.2 (4)	1.8 (6)
Direct Duct Exhaust Transition with anti blowback valve (Connection Ø 200mm/8")	KDD	Acc.	50078791	50073771		50078790		

#### User Convenience Options

We offer unique customer installed accessories to help organize your workspace and free up valuable space inside and around the BSC.

Hanging bar with set of 6 hooks	IVB 6 6	Acc.	50073943	No		No	
Hanging bar with set of 12 hooks	IVB 10 12	Acc.	No	50073944		50073944	
Utility basket to be used with hanging bar	KB	Acc.	50078900		50078900		
2 utility baskets incl. additional hanging bar	KBB	Acc.	50078901		50078901		

Additional topboxes for fumigation		Cat. No.	m (ft)
KSF frame fixed to top of each recirc cabinet to accept the relevant topbox for fumigation. Brackets are fitted to side of frame to allow the use of speed clamps. Height = 50mm		KSF9	Acc.
		KSF12/15	Acc.
		KSF18	Acc.
KSNB topbox for use with Hydrogen Peroxide fumigation. Speed clamps allow for fixture to a KSF frame. The 35mm hole will accept a Steris OR Bioquell outlet camlock fitting. Height = 110mm with gasket.		KSNB9	Acc.
		KSNB-12/15	Acc.
		KSNB-18	Acc.
KS-EVBOX for use with formonia system and formaldehyde. Speed clamps allow it to be clamped to KSF frame, while the 2 threaded holes accept the ABEKP3 charcoal filters. This box can only be used if the formaldehyde is being neutralized with ammonia after fumigation. Height = 110mm with gasket.		KS-EVBOX-9	Acc.
		KS-EVBOX-12/15	Acc.
		KS-EVBOX-18	Acc.
KSDB for use with formaldehyde fumigation only. Speed clamps allow for fixture to a KSP frame. This top box is supplied with a 3m flexi trunking which allows you to vent formaldehyde out into another exhausted application to purge fumes from cabinet. Side exit only. Height = 190mm with gasket.		KS9DB160	Acc.
		KS12DB160	Acc.
		KS18DB160	Acc.
KSP(FD) For use with formaldehyde fumigation. Fixes to a KSF frame. Supplied with a 3m flexi trunking which allows venting of fumes to an exhausted application. Top exit only. Height = 50mm (Frame).		KSP(FD)-9	Acc.
		KSP(FD)-12/15	Acc.
		KSP(FD)-18	Acc.
ABEKP3 charcoal filters screw into KS-EVBOX. Pack comprises of 3 filters.		ABEKP3	Acc.

Maxisafe 2030i BSC Ordering Information		EN 12469 & DIN12980				
<b>Dimensions</b>						
Size/Internal width		m (ft)	0.9 (3)	1.2 (4)	1.5 (5)	1.8 (6)
200mm Sash with Cross Beam UV-C in side walls			51032715	51032716	51032717	51032718
200mm Sash – no options included**			51032711	51032712	51032713	51032714
External Dimension (Cabinet only)	depth	mm (in.)	870 (34.3)	870 (34.3)	870 (34.3)	870 (34.3)
	width	mm (in.)	1000 (39.4)	1300 (51.2)	1600 (63.0)	1900 (74.8)
	height	mm (in.)	1536 (60.5)	1536 (60.5)	1536 (60.5)	1536 (60.5)
Usable Work Surface (net, without air intake grill)	depth	mm (in.)	465 (18.3)	465 (18.3)	465 (18.3)	465 (18.3)
	width	mm (in.)	900 (35.4)	1200 (47.2)	1500 (59.1)	1800 (70.9)
Shipping Dimension	depth	mm (in.)	970 (38.2)	970 (38.2)	970 (38.2)	970 (38.2)
	width	mm (in.)	1305 (51.4)	1605 (63.2)	1905 (75.0)	2205 (86.8)
	height	mm (in.)	1750 (68.9)	1750 (68.9)	1750 (68.9)	1750 (68.9)
Working height of front window		mm (in.)	200 (8)			
Maximum window opening (for cleaning, loading/unloading)		mm (in.)	773 (30.4)	773 (30.4)	773 (30.4)	773 (30.4)
Work surface height		mm (in.)	750-950 (29.5-37.4)			
<b>Weight</b>						
Net weight		kg (lbs)	200 (440)	240 (528)	280 (616)	330 (728)
Shipping weight		kg (lbs)	220 (484)	265 (583)	310 (682)	365 (803)
Max load capacity of one-piece work surface		kg (lbs)	50 (110)	50 (110)	50 (110)	50 (110)
Max load capacity of single segmented work surfaces (per 30cm segment)		kg (lbs)	25 (55)	25 (55)	25 (55)	25 (55)
<b>Electrical Data</b>						
Voltage		V	230 (except NA option*)			
Hertz		Hz	50/60			
Protection class			1/IP20			
<b>Filter Specification</b>						
Specification			H14 HEPA EN1822, 99.995% MPPS			

Maxisafe 2030i BSC Ordering Information		EN 12469 & DIN12980				
Size/Internal width	m (ft)	0.9 (3)	1.2 (4)	1.5 (5)	1.8 (6)	
<b>Certifications</b>						
Standard	EN 12469 & DIN 12980					
Agency certified		TÜV	TÜV	TÜV	TÜV	
<b>Ergonomics and Utilities</b>						
Lighting intensity	lux (fc)	1000 (93)	929 (86)	1500 (139)	1418 (132)	
Interior outlets	pcs.	2 rear wall		4 rear wall		
Service valve ports	pcs.	2 on each side + Smart Port				
Slope of front window	degree °	10				
<b>Maxisafe 2030i Specifications</b>						
Noise level (measured according to EN 12469)	dB (A)	57	59	59		
Power consumption (in normal operation, fans on, lights on)	W/h	230	240	390	390	
Power consumption (in night set back mode if available, lights off)	W/h	55	55	80	80	
Normal heat output in operation mode (non-vented)	W/h	230	240	390	390	
Reduced Flow Heat Output (lights off, non-vented)	W/h	55		80		
Exhaust volume of cabinet	m <sup>3</sup> /h (cf/m)	288 (169)	386 (227)	483 (284)	580 (341)	
Exhaust volume, thimble ducting	m <sup>3</sup> /h (cf/m)	385 (226)	513 (302)	641 (377)	770 (453)	
Size/Internal width	m (ft)	0.9 (3)	1.2 (4)	1.5 (5)	1.8 (6)	
<b>Receptical Orders</b>						
Country configurations are available to ensure correct line cord and internal receptacles are shipped with the cabinet. Standard version is Schuko if no other country version is specified						
Country Version Switzerland	Option	51900300				
Country Version UK	Option	51900303				
Country Version Italy	Option	51900306				
Country Version FR/B/CZ/SK/PL	Option	51900921				
Country Version Australia	Option	51900449				
Country Version Denmark	Option	51900481				
Country Version China	Option	51900900				
Country Version Israel	Option	51901255				
Country Version India	Option	51901261				
Country Version USA (NA 120V*)	Option	51901281				
Country Version Argentina	Option	51900308				
Country Version Chile	Option	51901259				
Country Version Brazil	Option	51901260				
A height adjustable stand is included with the Triple Filter BSC providing working height between 680mm-880mm						
<b>Work Surface Options</b>						
You have the option to fully customize your BSC to accommodate any work task. The standard EN/DIN cabinet includes a single piece indented 316 stainless steel work tray. Any of the options below or combinations are available for the Maxisafe 2030i, but note that the DIN12980 certification is negated on anything but the indented version we include as standard.						
without table tops (negative price)		Option	51900651	51900652	51900653	51900654
Flat Worksurface module (150 mm)	KAM15	Acc.	50073666			
Flat Worksurface module (300 mm)	KAM30	Acc.	50072685			
Flat Worksurface module (600 mm)	KAM60	Acc.	50073667			
Flat Worksurface module (900 mm)	KAM90	Acc.	50076398			
Flat worksurface module (1200mm)	KAM120	Acc.	No	50082970		
Flat worksurface module (1500mm)	KAM150	Acc.	No		50122210	
Flat worksurface module (1800mm)	KAM180	Acc.	No			50085281
Indented Worksurface module (600 mm)	KAML60	Acc.	50073668			
Indented Worksurface module (900 mm)	KAML90	Acc.	50073669			
Indented Worksurface module (1200 mm)	KAML120	Acc.	No	50073670		
Indented Worksurface module (1500 mm)	KAML150	Acc.	No		50073671	
Indented Worksurface module (1800 mm)	KAML180	Acc.	No			50078750
Vibration dampening granite block section (300mm width)	WP3	Acc.	50084339			
Vibration dampening granite block section (600mm width)	WP6	Acc.	50084350			
3 liter mini-sink table top module	KAMS30	Acc.	50078875			

**Maxisafe 2030i BSC Ordering Information**

EN 12469 & DIN12980

Size/Internal width	m (ft)	0.9 (3)	1.2 (4)	1.5 (5)	1.8 (6)
---------------------	--------	---------	---------	---------	---------

**Alternative 300 mm segmented work trays**

If 300 mm segmented work trays are required instead of the one piece deep-drawn work tray in the Maxisafe 2030i series, then the following shortcut SKU's can be used and the individual work trays will be factory installed. Note that DIN12980 is negated by selecting this option.

300mm segmented work trays (factory installed)	51901421	51901422	51901423	51901424
--	----------	----------	----------	----------

**Additional Work Surface Options**

Replacement armrests KAS 30 (Set of 2 arm rests 316 SS)	KAS 30	50073663
Padded armrest 316 SS (Set of 2 including gel inserts)	Acc.	50156438
Replacement gel pads for padded armrest (2 pcs.)	Acc.	50156437

**Additional Filter Options**

If Activated Carbon Filters are required in addition to Hepa filters on the Maxisafe series, the pre-filter bank can be substituted using our selectable option. Activated Carbon Filters will be factory fitted in place of the Hepa pre-filter bank beneath the work surface area.

Activated Carbon Pre-Filter set. Factory installed.	Option	51901411	51901412	51901413	51901414
---	--------	----------	----------	----------	----------

**UV Options**

The UV control function is designed to preserve bulb life whilst monitoring constantly. The light is programmable via the user interface. This feature measures and tracks UV bulb use ensuring that the bulbs will not require excessive replacement due to premature and unnecessary degradation. Additionally by monitoring UV bulb age, the system auto-adjusts run time to ensure consistent sterilization.

Cross beam UV-C light option is side walls includes protective cover

Included in models: 51032715, 51032716, 51032717, 51032718	Standard	Standard (Cross Beam - in Side Walls)
Available for models: 51032711, 51032712, 51032713, 51032714	Option	51900642 (Cross Beam - in Side Walls)

**Media Valves**

Our standard BSCs feature a dual-side wall negative pressure design which allows the user to install service valves through the side access ports. We also offer factory-installed piping options on our premium units to connect utilities to the top of the BSC to conserve right to left exterior footprint.

**Rear Wall Media Connections**

3 Utility Connectors prep (rear wall)-Select rear wall service taps additionally	Option	
Available for models: 51032711, 51032712, 51032713, 51032714	Option	51901251 (G3/8")
Available for USA country versions	Option	51901252 (NPT3/8)

**Rear Wall Service Taps/Media Valves (supplies are connected above BSC)**

Combustible Gas Tap for rear wall	Acc.	50068235
Non-combustible Gas Tap for rear wall	Acc.	50068234
Water Tap for rear wall	Acc.	50068233
Vacuum Tap for rear wall	Acc.	50068232

**Side Wall Service Taps/Media Valves/Lead Throughs**

Combustible Gas Tap for side wall	Acc.	50046015
Non-combustible Gas Tap for side wall	Acc.	50045959
Water Tap for side wall	Acc.	50044679
Vacuum Tap for side wall	Acc.	50044678
Hose connection for side wall, hose dia 10-13 mm	Acc.	50059017
Hose connection for side wall, hose dia 3 mm	Acc.	50076408
Hose connection for side wall, hose dia 6/3 mm	Acc.	50066668

**Solenoid Valve (Should be quoted with combustible gas G3/8 connection)**

Solenoid Valve for Combustible Gas Tap	Acc.	50074905
--	------	----------

Not all BSCs are manufactured to the same safety standards. Our design philosophy is grounded in compliance with the recognized worldwide safety standards, because your work cannot compromise on safety. Our biological safety cabinets are subjected to all the following certifications:



EN 12469

Our Class II biological safety cabinets are independently GS certified according EN 12469 by TÜV Nord.



NF EN 12469

Our Herasafe 2030i class II biological safety cabinet (1.2 m model) has been independently tested and certified to EN 12469 with the NF mark by LNE.



NSF

Our Class II biological safety cabinets are independently tested and certified to NSF/ANSI 49, by NSF International.

Learn more at [thermofisher.com/bsc](http://thermofisher.com/bsc)

**thermo** scientific

**For Laboratory Use. It is the customer's responsibility to ensure that the performance of the product is suitable for customers' specific uses or applications.** © 2022 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries unless otherwise specified. **EXT2177 0222**